



05000DPF Motor Oil 5W-30 Premium Synthetic C3 DPF

Document version: May 20, 2024



Description

This premium synthetic motor oil has been specially developed for BMW and Mercedes-Benz engines. This motor oil has the approvals of BMW Long Life 04 and Mercedes-Benz Long Life 229.51 / 229.52.. This SAE 5W-30 motor oil with ACEA C3 standard is recommended for petrol and diesel engines fitted with exhaust gas after-treatment systems.

Application manual

According to the specifications of

ACEA C3
API SN Plus / SP
BMW LL-04
Chrysler MS 11106
Fiat 9.55535-S3
GM dexos 2
MB-Approval 229.51 / 229.52
Opel OV 040 1547 - D30 / OV 040 1547 - G30
Renault RN 0700 / RN 0710
VW 502.00 / 505.00 / 505.01

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
05001DPF	1 L	6	450
05005DPF	5 L	4	112
05020DPF	20 L	1	-
05B20DPF	20 L	1	-
05060DPF	60 L	1	-
05205DPF	205 L	1	2
05999DPF	1000 L	1	-
P05000DPF	1 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.850	kg/l	ASTM D4052
Viscosity	5W-30		SAE
Kinematic Viscosity at 40°C	67.1	mm ² /s	ASTM D445
Kinematic Viscosity at 100°C	12.2	mm ² /s	ASTM D445
Viscosity Index	182		ASTM D2270
Dynamic Viscosity at -30°C	5400	mPa.s	ASTM D5293
Flashpoint COC	234	°C	ASTM D92
Pourpoint	-39	°C	ASTM D6892
Total Base Number	8.0	mgKOH/g	ASTM D2896
Sulphated Ash	0.77	mass%	ASTM D874

These characteristics are typical of current production. Variations in these characteristics may occur.