



## 18000MTF Gearbox Oil 75W-80 GL-5 Premium Synthetic MTF

Document version: May 20, 2024



### Description

This premium synthetic SAE 75W-80 transmission oil is specially recommended for various transmissions from car manufacturers such as Alfa Romeo, Fiat, Lancia, BMW, Opel, Peugeot, Renault and Volvo. This oil is used by various manufacturers as a 'fill for life' product.

### According to the specifications of

API GL-5  
Alfa Romeo  
BMW MTF-1 / MTF-2 / MTF-3  
Citröen  
Fiat 9.55550-MZ12 / 9.55550-MZ5  
Lancia  
Opel/GM 1940 757 / 1940 768 / 1942 776  
Peugeot  
Renault  
Volvo 97308

### Packaging units

| ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 18001MTF | 1 L    | 6              | 450              |
| 18004MTF | 4 L    | 4              | 112              |
| 18020MTF | 20 L   | 1              | 30               |
| 18060MTF | 60 L   | 1              | 6                |
| 18205MTF | 205 L  | 1              | 2                |
| 18999MTF | 1000 L | 1              | -                |

## Standard analyses

| TEST                         | VALUE  | METHOD             |
|------------------------------|--------|--------------------|
| Density at 15°C              | 0.887  | kg/l               |
| Viscosity                    | 75W-80 |                    |
| Kinematic Viscosity at 40°C  | 49.8   | mm <sup>2</sup> /s |
| Kinematic Viscosity at 100°C | 9.4    | mm <sup>2</sup> /s |
| Viscosity Index              | 175    |                    |
| Dynamic Viscosity at -40°C   | 37000  | mPa.s              |
| Flashpoint COC               | 190    | °C                 |
| Pourpoint                    | -48    | °C                 |

These characteristics are typical of current production. Variations in these characteristics may occur.