



## 16000DCTF Double Clutch Transmission Fluid

Verzija dokumenta: 15.04.2024.



### opis

Ova posebna tekućina za prenos razvijena je isključivo za Porsche i S-Tronic (kvačila u modelima Audi Quattro).

### Prema specifikacijama

VW G 052 529

### Jedinice pakovanja

ART. BR.	KOLIČINA	KOMADA PO JEDINICI	KOMADA PO PALETI
16001DCTF	1 L	6	450
16004DCTF	4 L	4	112
16020DCTF	20 L	1	30
16060DCTF	60 L	1	6
16205DCTF	205 L	1	2
16999DCTF	1000 L	1	-

### Standardne analize

TEST	VREDNOST		METHOD
Density na 15°C	0.849	kg/l	ASTM D4052
Colour	Green		
Kinematic Viscosity na 40°C	36.3	mm <sup>2</sup> /s	ASTM D445
Kinematic Viscosity na 100°C	7.3	mm <sup>2</sup> /s	ASTM D445
Viscosity Index	171		ASTM D2270
Dynamic Viscosity na -40°C	11000	mPa.s	ASTM D2983
Flashpoint	200	°C	ASTM D92
Pourpoint	-50	°C	ASTM D6892

Ove karakteristike su tipične za tekuću proizvodnju. Može doći do varijacija u ovim karakteristikama.