



16000HFM ATF Automatic Transmission Fluid HFM

Verzija dokumenta: 22.04.2024.



opis

Ovo vrhunsko sintetičko ulje za automatske mjenjače sa modifikatorima trenja, posebno je razvijeno za sve Audi, VW, Porsche, Volvo, Toyota, Lexus i Saab modele sa Aisin Warner automatskim mjenjačima.

Prema specifikacijama

Aisin Warner JWS 3309 / JWS 3314 / JWS 3317
BMW ETL-7045E / ETL-8072B
Fiat 9.55550-AV1
Ford Mercon-V / WSS-M2C202-B
Honda ATF Z1
Hyundai ATF SP-III / ATF SP-IV
KIA SP-III / SP-IV
Mitsubishi Diamond SP-II / Diamond SP-III
Nissan Matic D / Matic J / Matic K
Opel/GM 1940 773
Saab JWS 3309
Suzuki JWS 3309
Toyota T / T-III / T-IV
VW G 055 025
Volvo 1161540

Jedinice pakovanja

ART. BR.	KOLIČINA	KOMADA PO JEDINICI	KOMADA PO PALETI
16001HFM	1 L	6	450
16004HFM	4 L	4	112
16020HFM	20 L	1	30
16060HFM	60 L	1	6
16205HFM	205 L	1	2
16999HFM	1000 L	1	-

Standardne analize

TEST	VREDNOST	METHOD
Density na 15°C	0.849	kg/l
Colour	red	
Viscosity	10W	
Kinematic Viscosity na 40°C	35.6	mm ² /s
Kinematic Viscosity na 100°C	8.1	mm ² /s
Viscosity Index	212	
Brookfield Viscosity na -40°C	12000	mPa.s

Ove karakteristike su tipične za tekuću proizvodnju. Može doći do varijacija u ovim karakteristikama.