



16000ZF6S ATF Automatic Transmission Fluid ZF6/8/9 Special

Verzija dokumenta: 22.04.2024.



opis

Ovo vrhunsko sintetičko ATF ZF6 Special automatic transmission ulje je posebno namijenjeno za upotrebu u odabranim šestostepenim automatskim mjenjačima.

Prema specifikacijama

BMW 83 22 2 152 426
Chrysler 68157995A
Fiat 9.55550-AV5
Jaguar 02JDE26444
Land Rover LR023288
Rolls-Royce 83 22 2 152 426
VW G 060 162

Jedinice pakovanja

ART. BR.	KOLIČINA	KOMADA PO JEDINICI	KOMADA PO PALETI
16001ZF6S	1 L	6	450
16004ZF6S	4 L	4	112
16020ZF6S	20 L	1	30
16060ZF6S	60 L	1	6
16205ZF6S	205 L	1	2
16999ZF6S	1000 L	1	-

Standardne analize

TEST	VREDNOST		METHOD
Density na 15°C	0.848	kg/l	ASTM D4052
Colour	green		Visual
Viscosity 10W			
Kinematic Viscosity na 40°C	28.1	mm ² /s	ASTM D445
Kinematic Viscosity na 100°C	5.94	mm ² /s	ASTM D445
Viscosity Index	164		ASTM D2270
Dynamic Viscosity na -40°C	9500	mPa.s	ASTM D5293
Flashpoint COC	210	°C	ASTM D92
Pourpoint	-48	°C	ASTM D97

Ove karakteristike su tipične za tekuću proizvodnju. Može doći do varijacija u ovim karakteristikama.