



83000C Coolant -38°C G11 Ready to Use

Document version: May 20, 2024



Description

This silicate containing coolant -38 °C VW TL 774C/G11 is a top quality coolant and can be used throughout the whole year in the cooling systems of petrol and diesel engines. Thanks to the special additive package and the high quality mono-ethylene glycol this MPM Coolant -38 °C VW TL 774C/G-11 is one of the highest quality on the market. This coolant should be used undiluted and protects against freezing down to -38 °C. Does not contain nitrates, amines nor phosphates.

According to the specifications of

ASTM D3306 (USA)
BEHR (Radiators)
BMW GS 94000 / N600 69 0
CUNA NC956-16
Deutz/MWM
GM/Opel
MB 326.0
ONORM V5123
UNE 26-361
VW TL 774C G11

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
83001C	1 L	6	450
83005C	5 L	4	112
83020C	20 L	1	30
83060C	60 L	1	12
83205C	205 L	1	2
83999C	1000 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density	1.076	kg/l	
Colour	blue / green		
Frost Protection	-38	°C	
Copper Corrosion	8		

These characteristics are typical of current production. Variations in these characteristics may occur.