



# 05000ST Motor Oil 5W-30 Premium Synthetic ST

Document version: May 20, 2024



## Description

This Premium Synthetic 'Mid SAPS ' engine oil is designed for gasoline and diesel engines equipped with an exhaust after-treatment system. This special formulation complies with the Stellantis FPW9.55535/03 specification, which is mandatory for DV5R engines up to OPR 16885 and for the EB2 Gen1 (2013-2019) 1.2L PureTech engines. These D5VR and EB2 engines are used in Citroën, DS, Peugeot, Fiat, Toyota, Opel and Vauxhall. Optimized cleanliness reduces wear and increases the lifetime of the mechanical components and engine. This engine oil is also suitable for engines requiring the PSA B71 2290 specification with viscosity grade 5W-30.

## Application manual

## According to the specifications of

ACEA C3  
API SN Plus  
PSA B71 2290  
Stellantis FPW9.55535/03

## Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
05001ST	1 L	6	450
05005ST	5 L	4	112
05020ST	20 L	1	30
05060ST	60 L	1	6
05205ST	205 L	1	2
P05000ST	1 L	1	-

## Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.847	kg/l	ASTM D4052
Kinematic Viscosity at 40°C	66.3	mm <sup>2</sup> /s	ASTM D445
Kinematic Viscosity at 100°C	11.3	mm <sup>2</sup> /s	ASTM D445
Viscosity Index	170		ASTM 2270
Flashpoint COC	254	°C	ASTM D92
Pourpoint	-42	°C	ASTM D97

These characteristics are typical of current production. Variations in these characteristics may occur.