



16000FM ATF Automatic Transmission Fluid FM+

Document version: May 20, 2024



Description

This premium synthetic automatic transmission oil with added friction modifier has been specially developed for all Audi, VW, BMW, Jaguar and Porsche models (amongst other things) with a Tiptronic automatic transmission.

According to the specifications of

BMW LT 71141
Citroën ATF LT 71141
Fiat 9.55550-AG2
Jaguar ATF LT 71141
Land Rover ATF N 402
MB 236.11
PSA P/N Z000169752
Peugeot ATF LT 71141
Porsche ATF LT 71141
VW G 052 162
VW LT 71141
VW TL 52 162

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
16001FM	1 L	6	450
16004FM	4 L	4	112
16020FM	20 L	1	30
16060FM	60 L	1	6
16205FM	205 L	1	2
16999FM	1000 L	1	-

Standard analyses

TEST	VALUE	METHOD
Density at 15°C	0.849	kg/l
Colour	clear yellow / brown	
Viscosity	10W	
Kinematic Viscosity at 40°C	36.6	mm ² /s
Kinematic Viscosity at 100°C	7.2	mm ² /s
Viscosity Index	165	
Flashpoint COC	212	°C
Pourpoint	-48	°C
Total Base Number	2.7	mgKOH/g
Brookfield Viscosity at -40°C	12000	mPa.s

These characteristics are typical of current production. Variations in these characteristics may occur.