



# 16000MB9 ATF Automatic Transmission Fluid MB9 MB-236.17

Document version: May 20, 2024



## Description

This Premium Synthetic automatic transmission oil has been specially developed for the latest generation 9-speed automatic transmission from Mercedes-Benz where the MB 236.17 is mandatory recommended. This high quality transmission oil has a very high stable viscosity index, provides excellent protection against wear, corrosion and foaming, and due to the very low pour point provides very good lubrication at extremely low temperatures.

Due to the excellent properties as listed above, this oil has very low internal friction in the automatic gearbox which has a fuel-saving operation.

MPM Automatic Transmission Fluid MB9 with MB 236.17 can also be used where MB 236.16 is recommended. However, this high quality product with MPM Mercedes-Benz 236.17 specification can absolutely not be used for automatic gearboxes where earlier specifications such as MB 236.10, 236.12, 236.14 and / or MB 236.15 are prescribed.

MB 236.17

According to the specifications of

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
16001MB9	1 L	6	450
16004MB9	4 L	4	112
16020MB9	20 L	1	30
16060MB9	60 L	1	6
16205MB9	205 L	1	2
16999MB9	1000 L	1	-

## Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.822	kg/l	ASTM D4052
Kinematic Viscosity at 40°C	18	mm <sup>2</sup> /s	ASTM D445
Kinematic Viscosity at 100°C	4.1	mm <sup>2</sup> /s	ASTM D445
Viscosity Index	132		ASTM D2270
Flashpoint COC	212	°C	ASTM D92
Brookfield Viscosity at -40°C	4500	mPa.s	ASTM D2983

These characteristics are typical of current production. Variations in these characteristics may occur.