



51000C Fork Oil Medium Heavy 15W Premium Synthetic

Document version: May 20, 2024



Description

MPM Motorcycle Fork Oil Medium Heavy 15W Premium Synthetic is specially developed for use in telescopic front forks for mopeds and road/off road motorcycles. The high deaeration properties of this fork oil means that there is minimum reduced foaming in the fork legs bodies. This gives optimal performance and stability so it will maintain optimal performance under extreme road/off-road conditions. MPM 15W Fork Oil provides excellent protection against wear and corrosion of suspension elements and seals, resulting in a higher performance level.

Note: Also suitable for telescopic forks of mountain bikes and bicycles where a SAE 15W oil is required.

According to the specifications of

SAE 15W

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
51001C	1 L	6	450
51020C	20 L	1	30
51060C	60 L	1	6
51205C	205 L	1	2
51999C	1000 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.855	kg/l	ASTM D4052
Colour	Blue		VISUAL
Viscosity	15W		
Kinematic Viscosity at 40°C	43.2	mm ² /s	ASTM D445
Kinematic Viscosity at 100°C	8.62	mm ² /s	ASTM D445
Viscosity Index	183		ASTM D2270
Pourpoint	-48	°C	ASTM D

These characteristics are typical of current production. Variations in these characteristics may occur.