



87000ABV Antifreeze Premium Longlife BMW / Volvo Concentrate

Document version: May 20, 2024



Description

This Premium Long-Life antifreeze is silicate-containing, based on OAT, which among other specifications meets the latest requirements of BMW / Volvo models from 2018 onwards. This concentrate is also suitable for BMW / Volvo models from 1987 onwards.

This Premium Long-Life antifreeze should be diluted with the recommended quantity of demineralized water before use.

This antifreeze is also free from nitrites, amines, phosphate, borates and 2-ethylhexanoic acid.

Application manual

Freezing Point 33 vol % diluted -18°C (first crystal) Freezing Point 50 vol % diluted -38°C (first crystal) Freezing Point 60 vol % diluted -50°C (first crystal)

According to the specifications of

BMW LC 18
Volvo TR-31854114-002

Packaging units

| ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 87001ABV | 1 L | 6 | 450 |
| 87005ABV | 5 L | 4 | 112 |
| 87020ABV | 20 L | 1 | 30 |
| 87060ABV | 60 L | 1 | 6 |
| 87205ABV | 205 L | 1 | 2 |
| 87999ABV | 1000 L | 1 | - |

Standard analyses

| TEST | VALUE | | METHOD |
|----------------------------|-----------|-------|---------------|
| Density at 20°C | 1.125 | kg/l | ASTM D4052 |
| Colour | Green | | |
| Freezing Point 50% diluted | -40 | °C | ASTM D1177 |
| Ph 50% diluted | 7.5 - 8.5 | | ASTM D1287 |
| Ph | 8.4 - 8.9 | | ASTM D1287 |
| Boiling Point | >170 | °C | ASTM D1120 |
| Water | max 5 | mass% | ASTM D1123 |

These characteristics are typical of current production. Variations in these characteristics may occur.